

CLAIMS

1. A method for providing security for a computer network, comprising:
- generating content sets for a computer associated with the network;
- determining whether a user should be routed to the generated content sets;
- 5 selecting one of the content sets if it is determined that the user should be
routed to the generated content sets; and
- routing the user to the selected generated content set.
2. The method as recited in claim 1, further comprising monitoring the activities of
10 the user with respect to the computer.
3. The method as recited in claim 2, further comprising preventing the user from
accessing files associated with said monitoring.
- 15 4. The method as recited in claim 2, further comprising preventing the user from
accessing processes associated with said monitoring.
5. The method as recited in claim 1, further comprising associating each generated
content set with a virtual computer.
- 20

6. The method as recited in claim 5, wherein selecting one of the content sets includes choosing a content set associated with a virtual computer requested to be accessed by the user.

5 7. The method as recited in claim 5, further comprising associating each generated content set with its own network interface.

8. The method as recited in claim 7, further comprising concealing from the user network interfaces not associated with the selected generated content set.

10

9. The method as recited in claim 5, further comprising concealing from the user network connections not associated with the selected generated content set.

15

10. The method as recited in claim 9, wherein concealing network connections includes receiving a request from the user to access a network connection, checking whether that network connection is associated with the selected generated content set, and if it is not associated with the selected generated content set, providing an indication that the network connection does not exist.

20

11. The method as recited in claim 9, wherein concealing network connections includes receiving a request from the user to access a network connection, checking whether that network connection is associated with the selected generated content set, and if it is not associated with the selected generated content set, transforming the request

into a request to access a network connection associated with the selected generated content set.

12. The method as recited in claim 5, wherein the computer is running on a Unix
5 operating system.

13. The method as recited in claim 12, wherein the computer is running on a Solaris operating system.

10 14. The method as recited in claim 1, wherein selecting one of the content sets includes choosing a content set associated with a service requested to be accessed by the user.

15 15. The method as recited in claim 14, wherein the service is telnet.

16. The method as recited in claim 1, wherein selecting one of the content sets includes choosing a content set not currently in use by another user.

17. The method as recited in claim 1, further comprising storing the packets sent by
20 the user.

18. The method as recited in claim 1, further comprising logging information concerning the files to which the user requests access.

26. The method as recited in claim 25, wherein the unauthorized service is telnet.

27. The method as recited in claim 1, further comprising receiving an indication that the user is no longer connected to the computer.

5

28. The method as recited in claim 27, further comprising determining whether to retain changes in the files of the computer that resulted from the user's activities.

29. The method as recited in claim 28, further comprising resetting the computer to
10 restore the computer and the selected generated content set to the condition they were in prior to the user being routed to the selected generated content set if it is determined the changes should not be retained.

30. The method as recited in claim 29, further comprising updating the selected
15 generated content set by generating additional content that appears to have been created during a time period during which the user was connected to the computer.

31. A method for providing security for a computer network, comprising:
generating content sets for a file system for a first computer associated
20 with the network;
creating a plurality of directories within the first computer;
copying the file system of the first computer into each of the directories;
and

routing a user who attempts to gain unauthorized access to a second computer associated with the network to a first of the directories in the first computer.

5 32. The method as recited in claim 31, further comprising routing a user who attempts to gain unauthorized access to a third computer associated with the network to a second of the directories in the first computer.

10 33. The method as recited in claim 31, further comprising associating at least one of the directories with a virtual computer.

34. The method as recited in claim 33, further comprising associating each virtual computer with a network interface.

15 35. A system for providing security for a computer network, comprising:
a computer configured to generate content sets for the computer, wherein the computer is associated with the network;
a plurality of network interfaces each associated with one of the content sets; and
20 a network device configured to determine whether a user should be routed to the generated content sets, select one of the generated content sets if it is determined that the user should be routed to the generated content, and to route the user to the selected generated content set.

